

TIMBERCARE® FACADE COLOR STAIN**SEMI-TRANSPARENT TINTABLE HIGH DURABILITY COATING FOR EXTERIOR WOODEN SURFACES**

Transforms and protects new or old wood surfaces from premature discoloration, mold and structural damage caused by UV or water absorption. It brings out the beauty of the wood and its natural tone, emphasizes the texture and pattern of wood.

forms an elastic vapor-permeable film on the surface, allows the tree to "breathe";

high protection against UV rays for long-term color retention;

durable weatherproof.

GENERAL FEATURES:

- UV resistant, prevent premature graying of wood surfaces
- Water repellent
- Durable and resistant to exterior weather conditions
- Does not crack, peel or blister
- Keeps the color of the treated surface bright for a long time
- Forms an elastic and vapor-permeable film on the surface
- Allows wood to breathe
- High coverage;
- Translucent wood finish
- Lead free
- For exterior use

TYPE OF SURFACE: all types of pressed wood (fibreboard, OSB, plywood, etc.), new or previously coated wooden surfaces.

WHERE TO USE:

- Suitable for all exterior wood: summer houses, trellises, fences, garden furniture and decor
- Doors and window joinery
- Shutters
- Claddings
- Fences
- Pergolas
- Balcony railings
- Roof fringes

Not suitable for floors.

VISUAL EFFECT / tinting: a semi-transparent color finish that emphasizes the grain of the wood.

Gloss: Semi-gloss

Tint base clear - base for tinting in any shades, including deep and dark shades.

Suitable for tinting with any European tinting systems.

Packaging Size:

0.75 l (0.72 l + 30 ml of free volume for colorants).

2.5 liters (2.4 liters + 100 ml of free volume for colorants).

Application Method: Brush

Number of Coats: 2 coats

Coverage (m²/L): 6-7 m² with 2 coats depending on wood type

Drying Time (at 20°C and 40-65% relative humidity):

Recoat: 24 hours

Complete Dry: 24 hours

Product Data:

Solid Content (% weight): 63 ± 1

Viscosity (DIN4, 20°C): 75" ± 2

Density (g/cm³): 1 ± 0,02

VOC (g/L): 378

Thinning: Ready to use, does not require thinning.

Surface Preparation:

- Remove any dirt, oil and wood dust from the surface.

New Wood Surfaces:

- Sand the surface with sandpaper #80/120.
- Thoroughly clean the generated dust.

Old Uncoated Wood Surfaces:

- Sand the weathered surface with sandpaper #80/120.
- Thoroughly clean the generated dust.

Coated Wood Surfaces:

- Do not apply the product directly on pre-coated surfaces.
- Remove the old paint/varnish from the surface completely with a sandpaper.
- Thoroughly clean the generated dust.

Application:

- The product is ready to use and does not require thinning.
- Stir the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- Apply the product in 2 coats by brush and wait 24 hours between coats.
- Perform a slight sanding with sandpaper #180/220 between coats.
- Wait 24 hours for complete dry.
- Apply in the direction of wood grain to get a homogeneous look.

Maintenance (when the same product had been used before):

- Do not apply the product directly on pre-coated surfaces.
- Clean the wood surface completely from dirt and oil and perform a slight sanding.
- Thoroughly clean the generated dust.
- Repeat same process as described in "Application" with 1 or 2 coats depending on weathering.
- Inspect annually and maintain as required.

Instructions:

- FOR EXTERIOR USE ONLY.
- NOT SUITABLE FOR FLOORINGS.
- Keep product closed when not in use.
- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.
- The moisture content of the wood should be max. 20%.
- Do not apply the product under direct sunlight or rain.
- Do not apply linseed oil, basecoat/primer, yacht varnish before or after TIMBERCARE® FACADE COLOR STAIN applied surfaces.
- The product should be stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with mineral spirits after the application.

Safety Precautions:

- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer contents to other containers for storage.
- Do not use empty cans for other purposes.
- To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying.
- Avoid contact with eyes and skin.
- Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.
- Dispose of contents/cans in accordance with national regulations.
- Please refer to the Safety Data Sheet (SDS) of the product for health and safety information.

Certificates:

- EN71-3 Toy Safety Certificate