

TIMBERCARE® EXTERIOR WOOD OIL**PROTECTIVE OIL FOR EXTERIOR WOODEN SURFACES**

2-in-1: Clear (transparent) / Tint Base can be used as a base for tinting.

- 1 coat oil impregnates, protects any wooden surfaces
- UV resistant, water-repellent coating
- ensures hard-wearing, dirt and water-repellent coating
- non-slip coating even after rain
- enhances the natural beauty of the wood
- for horizontal and vertical exterior surfaces

GENERAL FEATURES:

- 1 coat oil impregnates, protects any wooden surfaces
- One-coat protection, impregnates the wood, maintains its natural moisture, prevents it from drying out
- UV resistant, protects weathering, prevents warping and deformation of the wood
- Water repellent
- Non-film forming, hardens inside the tree, not on the surface (without leaving a film on the wooden surface)
- Penetrates deep into the wooden surface, protecting it from within
- Without cracking, flaking off, washing out later
- Protects the coating from mold, prevents the occurrence of blue timber
- Enhances the natural beauty and texture of the wood
- Non-slip coating even after rain
- Suitable for new, old or previously oiled wood
- Economical single-layer coating, saves time and money for a full cycle of work
- Lead-free
- Ready to use
- For exterior use.

TYPE OF SURFACE: suitable for new, old or previously oiled wood. Excellent as a coating for non-tinted wood, as well as a mean to renew the protective properties and color of previously tinted with oils surfaces

Do not apply to primed or pre-painted with enamel or acrylic surfaces, as these coatings exclude the possibility of penetration of protective oils into the wood.

WHERE TO USE: the perfect solution for protecting and transforming

- smooth and rough wood facades
- decks
- garden furniture
- windows and doors
- fences and more.

VISUAL EFFECT / tinting:

Clear oil / Tint Base: transparent color finish that emphasizes the grain of the wood.

Gloss: Satin sheen

Tint base clear - base for tinting in any shades, including deep and dark shades.

Suitable for tinting with any European tinting systems.

Clear oil

On a new, previously untinted wood: creates a satin finish with a slight golden tint on the surface. On very light color woods, such as pine, the color may be deeper gold.

On tinted wood: enhances the color of tinted wood, making it deeper.

Packaging Size: Clear oil (transparent) / Tint Base

0.75 l (0.675 l + 75 ml of free volume for colorants).

2.5 liters (2.25 liters + 250 ml of free volume for colorants).

Product Data:

Solid Content (% weight): $90,8 \pm 1$

Viscosity (DIN4, 20°C): $30'' \pm 2$

Density (g/cm³): $0,95 \pm 0,05$

VOC (g/L): 108

Application Method: Brush or roller

Number of Coats: 1 coat

Coverage (m²/L): 15-18 m² depending on wood type

Drying Time (at 20°C and 40-65% relative humidity):

Touch Dry: 4-6 hours

Complete Dry: 24 hours.

Thinning: Ready to use, does not require thinning.

Surface Preparation:

- Remove any dirt, oil and wood dust from the surface.

New Wood Surfaces:

- Sand the surface with sandpaper #80/120.
- Thoroughly clean the generated dust.

Old Uncoated Wood Surfaces:

Sand the weathered surface with sandpaper #80/120.

Coated Wood Surfaces:

- Do not apply the product directly on pre-coated surfaces.
- Remove the old paint/varnish from the surface completely with a sanding machine.
- Thoroughly clean the generated dust.

Application:

- The product is ready to use and does not require thinning.
- Stir the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- Apply the product in 1 coat by a brush or roller and remove the excess oil by brush for the best result.
- Apply in the direction of wood grain to get a homogeneous look.
- The treated surface may be stepped on after 24 hours.

Maintenance (when the same product had been used before):

- Do not apply the product directly on pre-coated surfaces.
- Clean the wood surface completely from dirt and oil and perform a slight sanding.
- Thoroughly clean the generated dust.
- Repeat same process as described in “Application”.
- Inspect annually and maintain as required.

Instructions:

- FOR EXTERIOR USE ONLY.
- Keep product closed when not in use.
- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.
- The moisture content of the wood should be max. 20%.
- Do not apply the product under direct sunlight or rain.
- The product should be stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with mineral spirits after the application.

Safety Precautions:

- OIL SOAKED FABRIC CAN BE SELF IGNITING. FABRICS SHOULD BE COMPLETELY SOAKED IN WATER AND DISPOSED OF AFTER BEING USED.
- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer cans to other containers for storage.
- Do not use empty package for other purposes.
- To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying.
- Avoid contact with eyes and skin.
- Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.
- Dispose of contents/cans in accordance with national regulations.
- Please refer to the Safety Data Sheet (SDS) of the product for health and safety information.

Certificates:

EN71-3 Toy Safety Certificate