

TIMBERCARE® KITCHENWARE OIL

CUTTING BOARD AND WOODEN KITCHENWARE OIL

TIMBERCARE® KITCHENWARE OIL – natural oil for coating wooden preparation tables, cutting boards, salad bowls, pizza trays and other kitchenware which is closely connected to foods.

GENERAL FEATURES:

- Non-toxic and completely safe coating after drying
- Tested & certified according to LFGB standard for food contact
- Odorless and does not contain VOC
- Easily applied by wiping
- Preserves and revives the natural appearance of wood
- Safe for kids (EN 71-3)
- Does not contain heavy metals and lead
- Environmentally friendly
- Ready to use
- For interior use.

TYPE OF SURFACE: for any untreated wooden surfaces

WHERE TO USE: Wooden kitchenware

- wooden preparation tables
- chopping boards
- salad bowls
- pizza trays
- other kitchenware, which is in contact with food

VISUAL EFFECT: colorless oil, with honey (light yellow) color. Dries to a colorless finish, that emphasizes the natural grain structure of the wood. Does not change the shade of the tinting oil when it is used as a top protective coating.

Color: Clear Natural look

Gloss: When polishing creates a uniform Satin sheen of the treated surface.

Packaging Size: 250 ml

Application Method: Cloth

Number of Coats: 1 coat

Coverage (m²/L): 30 m² depending on wood type and application method

Drying Time (at 20°C and 40-65% relative humidity):

Touch Dry: 15 minutes

Complete Dry: 24 hours

Full Cure: 7 days

Product Data:

Solid Content % (weight): 100 ± 2

Viscosity (DIN6, 20°C): 12" ± 2

Density (g/cm³): 0,95 ± 0,02

VOC (g/L): 0

Type: Natural oil based

Description: Natural oil developed for the maintenance of wooden kitchenware (cutting board, salad bowl, pizza serving trays) directly in contact with food.

Thinning: Ready to use, does not require thinning.

Surface Preparation:

- Remove any dirt, oil and wood dust from the surface.
- Do not use products like cellulose or polyurethane filler or primer before the application of the product.

Untreated Wooden Surfaces:

- Sand the surface according to the desired surface appearance. I.e., it is recommended to sand with #80/120 for a natural finish and #180/220 for a smoother texture.
- Thoroughly clean the generated dust from the surface.
- Remove the remaining dust with a damp cloth and wait until completely dry.

Oiled Wooden Surfaces:

- Clean the wood surface thoroughly with warm water and avoid any dirt or oil. After cleaning, let the wood dry for at least 8 hours.

Old Uncoated Wooden Surfaces:

- Clean the wood surface thoroughly with warm water and avoid any dirt or oil. After cleaning, let the wood dry for at least 8 hours.

Varnished Wooden Surfaces:

- Do not apply the product directly on pre-coated surfaces.
- Remove the old varnish from the surface completely with a sandpaper.
- Remove any dirt, oil, wood dust and old varnish residues from the surface.
- Sand the surface according to the desired surface appearance. I.e., it is recommended to sand with #120 for a natural finish and #180 to 300 for a smoother texture.
- Thoroughly clean the generated dust and remove it completely from the surface.

Application:

- Shake well the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- Apply generously on all sides of the wood with a lint-free cloth or paper towel.
- Leave the product on the surface for 30 minutes to be absorbed by the wood, then remove the excess oil on the surface with a lint-free cloth or paper towel until you get a feeling of dryness.
- The surface is ready to use after 24 hours.
- If a more saturated surface appearance is desired, a second coat can be applied by waiting 24 hours.
- When it is observed that the surface dries or starts to absorb water after a certain period of use, the application should be repeated for maintenance purposes.

Instructions:

- FOR INTERIOR USE ONLY.
- Do not apply products such as nitro, polyurethane basecoats or primers before Kitchenware Oil.
- Keep product closed when not in use.

- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.
- The moisture content of the wood should be below 12%.
- The area should be ventilated during and after the application to promote the drying.
- The product should not be applied when the weather or surface temperature is below 10°C.
- The oiled kitchenware should not be cleaned with ammonia containing cleaning materials.
- The product should be stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with soap and plenty of warm water or mineral spirits after application.
-

Safety Precautions:

- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer contents to other containers for storage.
- Do not use empty cans for other purposes.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.
- Dispose of contents/cans in accordance with national regulations.
- Please refer to the Safety Data Sheet (SDS) of the product for health and safety information.

Certificates:

- EN71-3 Toy Safety Certificate
- LFGB Food Contact Certificate