

TIMBERCARE® SAUNA OIL

PROTECTIVE COATING FOR WOODEN SURFACES IN SAUNAS

Penetrates deep into the wood, it is special for creating a protective coating for wooden surfaces in saunas.

GENERAL FEATURES:

- 1 coat protection
- Fast drying
- Beautiful natural finish
- Does not cause darkening on ThermoWood
- Penetrates deeply and nourishes the wood
- Non-film forming
- Water repellent
- Ensures hard-wearing, dirt and water-repellent coating, that gives the wood ability to breathe
- Durable elastic heat-resistant coating
- Does not stick, does not crack under high temperatures
- Non-toxic and completely safe coating after drying
- Child safe (EN 71-3 Certified)
- Low odor, environmentally friendly and safe
- Easy application
- Ready to use

TYPE OF SURFACE: for any untreated wooden surfaces.

WHERE TO USE: protective coating on various wooden surfaces in the saunas.

For wooden surfaces in steam rooms, bathrooms, dressing rooms: walls, ceilings, doors, partitions, sweating shelves, benches.

VISUAL EFFECT: transparent coating, keeps the natural tone of the wood.
Does not change the color of the thermally modified timber.

Color / gloss: Natural look

Description: New generation tinted water based hybrid oil for interior wooden surfaces

Type: Water based

Packaging Size: 0,75 L.

Application Method: Brush or roller

Number of Coats: 1 coat

Coverage (m²/L):

10-12 m² on softwoods,

15-18 m² on hardwoods (depending on wood type and application method).

Drying Time (at 20°C and 40-65% relative humidity):

Touch Dry: 30 minutes

Complete Dry: 16 hours

Product Data:

Solid Content % (weight): 34,13 ± 1

Viscosity (DIN4, 20°C): 12" ± 2

Density (g/cm³): 1,03 ± 0,02

VOC (g/L): 33

Thinning: Ready to use, does not require thinning.

Surface Preparation:

- Remove any dirt, oil and wood dust from the surface.

New Wood Surfaces:

- Sand the surface with sandpaper #80/120.
- Thoroughly clean the generated dust.

Old Uncoated Wood Surfaces:

- Sand the weathered surface with sandpaper #150/180

Coated Wood Surfaces:

- Do not apply the product directly on pre-coated surfaces.
- Remove the old paint/varnish from the surface completely with a sanding machine.
- Thoroughly clean the generated dust.

Application:

- The product is ready to use and does not require thinning.
- Stir the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- Apply the product in 1 coat by a brush or roller and remove the excess oil by brush for the best result.
- Apply in the direction of wood to get a homogeneous look.
- The treated surfaces may be stepped on after 24 hours.

Maintenance (when the same product had been used before):

- Do not apply the product directly on pre-coated surfaces.
- Clean the wood surface completely from dirt and oil and perform a slight sanding.
- Thoroughly clean the generated dust.
- Repeat same process as described in "Application".
- Inspect annually and maintain as required.

Instructions:

- Keep product closed when not in use.
- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.
- The moisture content of the wood should be max. 20%.
- Do not apply the product under direct sunlight or rain.
- Do not apply linseed oil, basecoat/primer, yacht varnish before or after SAUNA OIL applied surfaces.
- The product should be protected from freezing and stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with soap and plenty of warm water after application.

Safety Precautions:

- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN
- Do not transfer contents to other containers for storage
- Do not use empty cans for other purposes.
- To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying.
- Avoid contact with eyes and skin. Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists.
- If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.
- Dispose of contents/cans in accordance with national regulations.
- Please refer to the Safety Data Sheet (SDS) of the product for health and safety information.

Certificates:

- EN71-3 Toy Safety Certificate