

**TIMBERCARE® TEAK OIL****NOURISHES AND REVIVES OIL**

Natural TIMBERCARE® Teak Oil is specially prepared to protect and restore heavy woods such as teak, mahogany, etc.

Also suitable for soft woods.

**GENERAL FEATURES:**

- Penetrates deeply into the wood surface by feeding into the core of the timber, protecting the surface from within
- UV resistant
- Water repellent, protects wood, even on yachts above the waterline
- Salt water resistant coating
- Nourishes and revives, impregnates the wood, prevents it from drying out
- Renews and gives the wood more beautiful look, gives brightness
- Creates a warm, bright color of an rich handmade finish
- Protection against mold, rotting, shape changes, swelling or cracking of wood
- Easy maintenance
- Lead-free
- Ready to use
- For exterior use

**TYPE OF SURFACE:** for new, old or pressed wooden surfaces. For all types of wood, including exotic.

**Do not apply** to primed or pre-painted enamel or acrylic surfaces as these coatings exclude the possibility of penetration of protective oils into the wood. Not recommended for high-traffic floors and wood surfaces below the waterline.

**WHERE TO USE:**

- For exterior wood and garden furniture, wood facades, summer houses, decking, windows and doors, pergolas, fences
- Suitable for all exterior wood of boats and yachts above the waterline

**VISUAL EFFECT:**

Enhances the grain and texture of wood.

**Color:** Clear transparent Natural look

**Gloss:** Satin sheen

On a new, previously untinted wood: creates a satin finish with a slight golden tint on the surface. With very light color woods such as pine, dries to more deep caramel finish.

On tinted wood: makes the color of tinted wood deeper, brighter.

**Packaging Size:** 0,750 L., 2,5 L

**Application Method:** Brush or cloth

**Number of Coats:** 1 coat

**Coverage (m<sup>2</sup>/L):** 15-18 m<sup>2</sup> depending on wood type

**Drying Time (at 20°C and 40-65% relative humidity):**

Touch Dry: 4 hours

Complete Dry: 24 hours

**Product Data:**

Solid Content (% weight): 42,8 ± 1

Viscosity (DIN4, 20°C): 10" ± 2

Density (g/cm<sup>3</sup>): 0,85 ± 0,02

VOC (g/L): 482

**Type:** Oil-based

**Description:** Maintenance oil for exterior wood and garden furniture

**Thinning:** Ready to use, does not require thinning.

**Surface Preparation:**

Remove any dirt, oil and wood dust from the surface.

New Wood Surfaces:

- Sand the surface with sandpaper #80/120.
- Thoroughly clean the generated dust.

Old Uncoated Wood Surfaces:

- Sand the weathered surface with sandpaper #80

Coated Wood Surfaces:

- Do not apply the product directly on pre-coated surfaces.
- Remove the old paint/varnish from the surface completely with a sandpaper.
- Thoroughly clean the generated dust.

**Application:**

- The product is ready to use and does not require thinning.
- Stir the product thoroughly before use.
- Apply the product in 1 coat by a brush or cloth and remove the excess oil by cloth for the best result.
- Wait 24 hours for complete dry.

**Maintenance (when the same product had been used before):**

- Do not apply the product directly on pre-coated surfaces.
- Clean the wood surface completely from dirt and oil and perform a slight sanding.
- Thoroughly clean the generated dust.
- Repeat same process as described in "Application".
- Maintenance should be repeated every season.

**Instructions:**

- FOR EXTERIOR USE ONLY.
- Keep product closed when not in use.
- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.
- The moisture content of the wood should be max. 20%.
- Do not apply the product under direct sunlight or rain.
- The product should be stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with mineral spirits after the application.

**Safety Precautions:**

- OIL SOAKED FABRIC CAN BE SELF IGNITING. FABRICS SHOULD BE COMPLETELY SOAKED IN WATER AND DISPOSED OF AFTER BEING USED.
- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer contents to other containers for storage.
- Do not use empty plastic cans for other purposes.
- To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying.
- Avoid contact with eyes and skin.
- Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.
- Dispose of contents/plastic cans in accordance with national regulations.
- Please refer to the Safety Data Sheet (SDS) of the product for health and safety information.

**Certificates:**

EN71-3 Toy Safety Certificate